

View Online at <https://aerobasegroup.com/nsn/3416-00-998-8922>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

84.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

10.0

Bed Type:

Sliding gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+18.0/+720.0

Swing Over Cross Slide:

18.000 inches

Thread Change Quantity:

48

Rated Swing Through Open Gap:

52.000 inches

Actual Swing Through Open Gap:

52.000 inches

Rated Swing Over Closed Gap:

24.000 inches

Actual Swing Over Closed Gap:

26.500 inches

Err Default:

Err default

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

5 asa standard

Hole Diameter Through Spindle:

2.188 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+112.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Bas differentiated by center to center distance, distance between open centers, spindle speed range in rpm, elec motor quan, elec motor hp rating, current type, voltage in volts, freq in hertz, and phase

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b