

View Online at <https://aerobasegroup.com/nsn/3416-01-034-1257>

Mounting Type:

Bench or floor

Center To Center Distance:

30.000 inches

Performance Type:

Light duty

Accessory Components And Quantity:

1 stop, carriage, micrometer, 1 stop, thread cutting, 1 indicator, thread, 1 taper attachment, 1 set gears, 1 bag, 1 cover, canvas, 1 set wrenches, 1 wrench spanner, 1 wrench, tool post, 1 adapter headstock, 1 adapter, tailstock, 1 chuck, 3-jaw universal, 1 chuck 4 jaw independent, 1 chuck, collet, 1 set collets, 1 chuck drill, 1 faceplate, 12 inch diameter, 1 faceplate, 24 inch diameter, 2 lathe centers, 1 set dog lathe, 1 dog lathe, 1 steadyrest, 3 sockets, taper shank tool, 1 set drift, drill, 1 set tool post, lathe, 1 knurling tool, 2 holders, 3/8 inch squarecutter bit right and left hand turning, 2 holders, 1/8 x 7/8 inch cut-off blade, right and left hand offset, 1 holder, boring bar, 1 boring bar, round, 1/2 inch diameter, 1 boring bar round, 3/4 inch diameter, 1 boring bar, round, 1-1/8 inch diameter, 3 knurling sets

Electric Motor Horsepower Rating:

5.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+30.0/+1200.0

Rated Swing:

25.000 inches

Actual Swing Over Bed:

25.000 inches

Swing Over Cross Slide:

18.000 inches

Hole Diameter Through Spindle:

3.000 inches

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-h