

View Online at <https://aerobasegroup.com/nsn/3416-01-034-1257>

**Mounting Type:**

Bench or floor

**Center To Center Distance:**

30.000 inches

**Performance Type:**

Light duty

**Accessory Components And Quantity:**

1 stop, carriage, micrometer, 1 stop, thread cutting, 1 indicator, thread, 1 taper attachment, 1 set gears, 1bag, 1 cover, canvas, 1 set wrenches, 1 wrench spanner, 1 wrench, tool post, 1 adapter headstock, 1 adapter, tailstock, 1 chuck, 3-jaw universal, 1 chuck4 jaw independent, 1 chuck, collet, 1 set collets, 1 chuck drill, 1 faceplate, 12 inch diameter, 1 faceplate, 24 inch diameter, 2 lathe centers, 1 set dog lathe, 1 dog lathe, 1 steadyrest, 3 sockets, taper shank tool, 1 set drift, drill, 1 set tool post, lathe, 1 knurling tool, 2 holders, 3/8 inch squarecutter bit right and left hand turning, 2 holders, 1/8 x 7/8 inch cut-off blade, right and left hand offset, 1 holder, boring bar, 1 boring bar, round, 1/2 inch diameter, 1 boring bar round, 3/4 inch diameter, 1 boring bar, round, 1-1/8 inch diameter, 3 knurling sets

**Electric Motor Horsepower Rating:**

5.000

**Bed Type:**

Solid

**Electric Motor Quantity:**

1

**Spindle Speed Quantity:**

12

**Spindle Speed Range In Rpm:**

+30.0/+1200.0

**Rated Swing:**

25.000 inches

**Actual Swing Over Bed:**

25.000 inches

**Swing Over Cross Slide:**

18.000 inches

**Hole Diameter Through Spindle:**

3.000 inches

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-b