

View Online at <https://aerobasegroup.com/nsn/3416-01-108-8844>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

Between 54.000 inches and 132.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 thread dial, 1 chip pan, 8 in. D-1 cam-lock spindle

Design Type:

Screw

Electric Motor Horsepower Rating:

10.000

Bed Type:

Sliding gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+30.0/+1580.0

Swing Over Cross Slide:

9.500 inches

Thread Change Quantity:

60

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

5 morse

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand

Carriage Cross Feed Operation Method:

Hand

Gear Change Type:

Quick

Thread Quantity Range:

+1.0/+160.0 per inch

Voltage In Volts:

240.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b