
Engine Lathe - Page 1 of 2

Mounting Type:





Floor **Current Type:** Dc **Center To Center Distance:** 50.000 inches Performance Type: Standard duty **Purpose For Which Designed:** General Accessory Components And Quantity: 1 pump motor **Design Type:** Screw **Electric Motor Horsepower Rating:** 7.500 Bed Type: Solid **Electric Motor Quantity:** 1 **Spindle Speed Quantity:** 16 Spindle Speed Range In Rpm: +25.0/+2000.0 **Rated Swing:** Any acceptable **Actual Swing Over Bed:** 15.250 inches Swing Over Cross Slide: 9.500 inches **Thread Change Quantity:** 45 Headstock Drive Type: Geared head Headstock Center Taper Size Designator: 16 morse Hollow Spindle Hole Size: 2.188 inches **Carriage Quantity:** 1 **Carriage Longitudinal Feed Operation Method:** Power

NSN 3416-01-196-3793

Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:

Power

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+72.0 per inch

Voltage In Volts:

230.0 and 460.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T221-b