

View Online at <https://aerobasegroup.com/nsn/3416-01-207-3365>

**Mounting Type:**

Floor

**Current Type:**

Ac/dc

**Current Rating In Amps:**

55.0

**Design Type:**

Saddle

**Electric Motor Horsepower Rating:**

50.000 or 75.000

**Power Source:**

Electric motor

**Maximum Bar Stock Diameter Accommodated:**

6.500 inches

**Maximum Chucking Distance Over Universal Carriage:**

32.750 inches

**Spindle Speed Quantity:**

1188

**Spindle Speed Range In Rpm:**

+12.0/+1200.0

**Spindle Reversibility:**

Reversible

**Rated Swing:**

32.750 inches

**Actual Swing Over Bed:**

40.000 inches

**Swing Over Cross Slide:**

32.750 inches

**Maximum Distance From Spindle Nose To Turret Face:**

54.000 inches

**Universal Carriage Longitudinal Travel:**

60.000 inches

**Universal Carriage Cross Travel:**

14.400 inches

**Universal Carriage Feed Type:**

Power

**Err Default:**

Err default

**Err Default:**

Err default

**Universal Carriage Compound:**

Not included

**Turret Carriage Longitudinal Travel:**

60.000 inches

**Err Default:**

Err default

**Turret Carriage Feed Type:**

Power

**Err Default:**

Err default

**Turret Shape:**

Hexagon

**Turret Position Quantity:**

12

**Product Name:**

Lathe, chucking, computer numeric control

**Voltage In Volts:**

460.0

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T221-a