

View Online at <https://aerobasegroup.com/nsn/3416-01-207-3365>

Mounting Type:

Floor

Current Type:

Ac/dc

Current Rating In Amps:

55.0

Design Type:

Saddle

Electric Motor Horsepower Rating:

50.000 or 75.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

6.500 inches

Maximum Chucking Distance Over Universal Carriage:

32.750 inches

Spindle Speed Quantity:

1188

Spindle Speed Range In Rpm:

+12.0/+1200.0

Spindle Reversibility:

Reversible

Rated Swing:

32.750 inches

Actual Swing Over Bed:

40.000 inches

Swing Over Cross Slide:

32.750 inches

Maximum Distance From Spindle Nose To Turret Face:

54.000 inches

Universal Carriage Longitudinal Travel:

60.000 inches

Universal Carriage Cross Travel:

14.400 inches

Universal Carriage Feed Type:

Power

Err Default:

Err default

Err Default:

Err default

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

60.000 inches

Err Default:

Err default

Turret Carriage Feed Type:

Power

Err Default:

Err default

Turret Shape:

Hexagon

Turret Position Quantity:

12

Product Name:

Lathe, chucking, computer numeric control

Voltage In Volts:

460.0

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T221-a