

View Online at <https://aerobasegroup.com/nsn/3416-01-210-8184>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

40.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 5 hp motor and control; 1 thread dial indicator; 1 set of change gears; 1 no. 4 mt carbide tipped center; 1 no. 4 mt hardened center; 1 no. 6 mt spindle sleeve; 1 9 in. 3-jaw universal chuck with reversible top jaws; 1 foot-operated spindle brake; 1 tool post assembly; 1 7 in. Diameter face plate; 1 set wrenches; 1 automatic longitudinal stop; 1 coolant equipment; 1 traveling splash pan

Design Type:

Screw

Electric Motor Horsepower Rating:

5.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+59.0 to 1400.0

Rated Swing:

15.750 inches

Actual Swing Over Bed:

15.750 inches

Swing Over Cross Slide:

8.625 inches

Thread Change Quantity:

32

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

2.062 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand

Carriage Cross Feed Operation Method:

Hand

Gear Change Type:

Plain

Thread Quantity Range:

+4.0 to 56.0 per inch

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b