

View Online at <https://aerobasegroup.com/nsn/3416-01-213-5941>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

72.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Design Type:

Screw

Electric Motor Horsepower Rating:

60.000

Bed Type:

Solid

Electric Motor Quantity:

5

Spindle Speed Quantity:

1

Spindle Speed Range In Rpm:

+16.0/+1600.0

Rated Swing:

32.000 inches

Actual Swing Over Bed:

32.000 inches

Swing Over Cross Slide:

25.000 inches

Thread Change Quantity:

9999

Headstock Drive Type:

Gearhead

Headstock Center Taper Size Designator:

1 morse

Hollow Spindle Hole Size:

4.562 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Power

Carriage Cross Feed Operation Method:

Power

Gear Change Type:

Quick

Voltage In Volts:

230.0 and 460.0 and 575.0

Phase:

Three

Special Features:

Two tool turrets, each with 7 tool stations, acramatic 900tc control, feed rate 0-200 ipm, traverse rate 300 ipm; net weight 36,000 lbs

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b