

View Online at <https://aerobasegroup.com/nsn/3416-01-217-7908>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Current Rating In Amps:**

40.0

**Design Type:**

Saddle

**Electric Motor Horsepower Rating:**

30.000

**Power Source:**

Electric motor

**Maximum Bar Stock Diameter Accommodated:**

2.500 inches

**Maximum Chucking Distance Over Universal Carriage:**

10.000 inches

**Spindle Speed Quantity:**

3465

**Spindle Speed Range In Rpm:**

+35.0/+3500.0

**Spindle Reversibility:**

Reversible

**Rated Swing:**

10.000 inches

**Actual Swing Over Bed:**

19.000 inches

**Swing Over Cross Slide:**

10.000 inches

**Maximum Distance From Spindle Nose To Turret Face:**

24.000 inches

**Universal Carriage Longitudinal Travel:**

24.000 inches

**Universal Carriage Cross Travel:**

6.750 inches

**Universal Carriage Feed Type:**

Power

**Err Default:**

Err default

**Err Default:**

Err default

**Universal Carriage Compound:**

Not included

**Turret Carriage Longitudinal Travel:**

24.000 inches

**Err Default:**

Err default

**Turret Carriage Feed Type:**

Power

**Err Default:**

Err default

**Turret Shape:**

Hexagon

**Turret Position Quantity:**

16

**Product Name:**

Lathe, computer numeric control

**Voltage In Volts:**

208.0 and 480.0

**Phase:**

Three

**Special Features:**

Collant pump and plumbing

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-a