

View Online at <https://aerobasegroup.com/nsn/3416-01-217-7908>

Mounting Type:

Floor

Current Type:

Ac

Current Rating In Amps:

40.0

Design Type:

Saddle

Electric Motor Horsepower Rating:

30.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

2.500 inches

Maximum Chucking Distance Over Universal Carriage:

10.000 inches

Spindle Speed Quantity:

3465

Spindle Speed Range In Rpm:

+35.0/+3500.0

Spindle Reversibility:

Reversible

Rated Swing:

10.000 inches

Actual Swing Over Bed:

19.000 inches

Swing Over Cross Slide:

10.000 inches

Maximum Distance From Spindle Nose To Turret Face:

24.000 inches

Universal Carriage Longitudinal Travel:

24.000 inches

Universal Carriage Cross Travel:

6.750 inches

Universal Carriage Feed Type:

Power

Err Default:

Err default

Err Default:

Err default

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

24.000 inches

Err Default:

Err default

Turret Carriage Feed Type:

Power

Err Default:

Err default

Turret Shape:

Hexagon

Turret Position Quantity:

16

Product Name:

Lathe, computer numeric control

Voltage In Volts:

208.0 and 480.0

Phase:

Three

Special Features:

Collant pump and plumbing

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a