

View Online at <https://aerobasegroup.com/nsn/3416-01-228-3932>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

40.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 3-jaw chuck w/backplate, 4-jaw chuck w/backplate, 1 faceplate, 2 centers, coolant system; tool box, seady rest, follow rest, tool post

Design Type:

Plain

Electric Motor Horsepower Rating:

7.500

Bed Type:

Removable block gap

Electric Motor Quantity:

2

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+74.0/+1500.0

Swing Over Cross Slide:

9.625 inches

Rated Swing Through Open Gap:

23.375 inches

Actual Swing Through Open Gap:

23.375 inches

Rated Swing Over Closed Gap:

16.000 inches

Actual Swing Over Closed Gap:

16.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

6 morse

Hollow Spindle Hole Size:

2.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b