## NSN 3416-01-237-6063

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-01-237-6063

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
60.000 inches
Performance Type:
Heavy duty
Purpose For Which Designed:
Toolroom
Accessory Components And Quantity:
All accessories are optional
Design Type:
Screw
Electric Motor Horsepower Rating:
10.000
Bed Type:
Permanent gap
Electric Motor Quantity:
1
Spindle Speed Quantity:
16
Spindle Speed Range In Rpm:
+20.0/+1600.0
Rated Swing:
17.250 inches
Actual Swing Over Bed:
17.250 inches
Swing Over Cross Slide:
10.500 inches
Thread Change Quantity:
38
Headstock Drive Type:
Geared head
Headstock Center Taper Size Designator:
5 morse
Hole Diameter Through Spindle:
3.062 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:

Hand or power

## **NSN 3416-01-237-6063** Engine Lathe - Page 2 of 2



<b>Carriage Cross Feed Operation Method:</b>
Hand or power
Gear Change Type:
Quick
Thread Quantity Range:
+2.0/+72.0 per inch
Voltage In Volts:
230.0 and 460.0
Phase:
Three
Special Features:
Thrd rng .4-14mm w/thrd chg 40
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T221-b