NSN 3416-01-237-6063

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-01-237-6063

| Mounting Type: |
|--|
| Floor |
| Current Type: |
| Ac |
| Center To Center Distance: |
| 60.000 inches |
| Performance Type: |
| Heavy duty |
| Purpose For Which Designed: |
| Toolroom |
| Accessory Components And Quantity: |
| All accessories are optional |
| Design Type: |
| Screw |
| Electric Motor Horsepower Rating: |
| 10.000 |
| Bed Type: |
| Permanent gap |
| Electric Motor Quantity: |
| 1 |
| Spindle Speed Quantity: |
| 16 |
| Spindle Speed Range In Rpm: |
| +20.0/+1600.0 |
| Rated Swing: |
| 17.250 inches |
| Actual Swing Over Bed: |
| 17.250 inches |
| Swing Over Cross Slide: |
| 10.500 inches |
| Thread Change Quantity: |
| 38 |
| Headstock Drive Type: |
| Geared head |
| Headstock Center Taper Size Designator: |
| 5 morse |
| Hole Diameter Through Spindle: |
| 3.062 inches |
| Carriage Quantity: |
| 1 |
| Carriage Longitudinal Feed Operation Method: |

Hand or power

NSN 3416-01-237-6063 Engine Lathe - Page 2 of 2



| Carriage Cross Feed Operation Method: |
|--|
| Hand or power |
| Gear Change Type: |
| Quick |
| Thread Quantity Range: |
| +2.0/+72.0 per inch |
| Voltage In Volts: |
| 230.0 and 460.0 |
| Phase: |
| Three |
| Special Features: |
| Thrd rng .4-14mm w/thrd chg 40 |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T221-b |