

View Online at <https://aerobasegroup.com/nsn/3416-01-338-7667>

Mounting Type:

Bench

Current Type:

Ac

Center To Center Distance:

20.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

4 way tool box; instruction manual7.0 in. 4 jaw independent chuck; 4.0 in. 3 jaw universal chuck; steady rest

Design Type:

Screw

Electric Motor Horsepower Rating:

0.750

Bed Type:

Permanent gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

6

Spindle Speed Range In Rpm:

+130.0/+2000.0

Rated Swing:

9.000 inches

Actual Swing Over Bed:

9.000 inches

Swing Over Cross Slide:

5.313 inches

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

3 morse

Hole Diameter Through Spindle:

0.780 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+8.0/+56.0 per inch

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Linch/metric dial; thread dial; reversing switch; 32.0 in. Bed lg; 4.5 in. Bed wd; 37.5 in. Lg by 19.75 in. Wd by 15.75 in. Ht o/a; 195 lbs; stock number 115v, 321370; stock number 230v, 321371; max tool size 0.250 by 0.250

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b