NSN 3416-01-339-1239

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-01-339-1239

Mounting Type: Floor Current Type: Ac Center To Center Distance: 30.000 inches Performance Type: Heavy duty
Current Type: Ac Center To Center Distance: 30.000 inches Performance Type:
Ac Center To Center Distance: 30.000 inches Performance Type:
Center To Center Distance: 30.000 inches Performance Type:
30.000 inches Performance Type:
Performance Type:
· ·
Heavy duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
1 taper attachment
Design Type:
Screw
Electric Motor Horsepower Rating:
7.500
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
12
Spindle Speed Range In Rpm:
+45.0/+1800.0
Rated Swing:
15.000 inches
Actual Swing Over Bed:
15.500 inches
Swing Over Cross Slide:
9.500 inches
Thread Change Quantity:
48
Headstock Drive Type:
Direct pulley, back geared
Headstock Center Taper Size Designator:
4 morse
Hole Diameter Through Spindle:
2.281 inches
2.201 IIICHES
Carriage Quantity:

Power

NSN 3416-01-339-1239 Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Power
Gear Change Type:
Plain
Гhread Quantity Range:
+2.0/+112.0 per inch
/oltage In Volts:
230.0
Phase:
Гhree
Frequency In Hertz:
60.0
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
Г221-b