

View Online at <https://aerobasegroup.com/nsn/3416-01-339-1239>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

30.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 taper attachment

Design Type:

Screw

Electric Motor Horsepower Rating:

7.500

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+45.0/+1800.0

Rated Swing:

15.000 inches

Actual Swing Over Bed:

15.500 inches

Swing Over Cross Slide:

9.500 inches

Thread Change Quantity:

48

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

2.281 inches

Carriage Quantity:

3

Carriage Longitudinal Feed Operation Method:

Power

Carriage Cross Feed Operation Method:

Power

Gear Change Type:

Plain

Thread Quantity Range:

+2.0/+112.0 per inch

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b