

View Online at <https://aerobasegroup.com/nsn/3416-01-374-5650>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Performance Type:**

Heavy duty

**Purpose For Which Designed:**

General

**Accessory Components And Quantity:**

1center brush, 2 3mt centers, splash guard, coolant system, inch threading dial, wrench set and keys

**Design Type:**

Screw

**Electric Motor Horsepower Rating:**

10.000

**Bed Type:**

Removable block gap

**Rated Swing Through Open Gap:**

21.000 inches

**Actual Swing Through Open Gap:**

21.000 inches

**Headstock Center Taper Size Designator:**

3 morse

**Hollow Spindle Hole Size:**

1.656 inches

**Hole Diameter Through Spindle:**

3.000 inches

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

208v available; swing over cross slide 7.750; infinitely variable speed spindle drive; apron w/gated controls; 3 range headstock; hp at spindle 7.5; bed 12.5 in. Wd; cross slide tvl 10.0 in.; compound rest travel 4.00 in.; tailstock center 4mt; tailstock travel 5.75 in.; feeds per spindle rev 0.0012 - 0.08 in.; magnetic starter w/110v controls; qc tool post; steady rest; follower rest; micro bed stop; chuckguard; chipguard; taper attachment; 12.0 and 18.0 in. Face plate; 8.0 in. 3-jaw chuck; 8.0 in. 4-jaw chuck

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-h