

View Online at <https://aerobasegroup.com/nsn/3416-01-374-5650>

Mounting Type:

Floor

Current Type:

Ac

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1center brush, 2 3mt centers, splash guard, coolant system, inch threading dial, wrench set and keys

Design Type:

Screw

Electric Motor Horsepower Rating:

10.000

Bed Type:

Removable block gap

Rated Swing Through Open Gap:

21.000 inches

Actual Swing Through Open Gap:

21.000 inches

Headstock Center Taper Size Designator:

3 morse

Hollow Spindle Hole Size:

1.656 inches

Hole Diameter Through Spindle:

3.000 inches

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

208v available; swing over cross slide 7.750; infinitely variable speed spindle drive; apron w/gated controls; 3 range headstock; hp at spindle 7.5; bed 12.5 in. Wd; cross slide tvl 10.0 in.; compound rest travel 4.00 in.; tailstock center 4mt; tailstock travel 5.75 in.; feeds per spindle rev 0.0012 - 0.08 in.; magnetic starter w/110v controls; qc tool post; steady rest; follower rest; micro bed stop; chuckguard; chipguard; taper attachment; 12.0 and 18.0 in. Face plate; 8.0 in. 3-jaw chuck; 8.0 in. 4-jaw chuck

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b