

View Online at <https://aerobasegroup.com/nsn/3416-01-374-5651>

Mounting Type:

Floor

Current Type:

Ac

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1center brush, 2 mt centers, 1 splash guard, coolant system, inch threading dial, wrench set and keys

Design Type:

Screw

Electric Motor Horsepower Rating:

15.000

Bed Type:

Removable block gap

Spindle Speed Range In Rpm:

+20.0/+2000.0

Rated Swing Through Open Gap:

28.750 inches

Actual Swing Through Open Gap:

28.750 inches

Headstock Center Taper Size Designator:

5 morse

Hollow Spindle Hole Size:

3.000 inches

Hole Diameter Through Spindle:

3.000 inches

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

208 v available; swing over cross slide 10.625; infinitely variable speed spindle drive; saddle mounted controls; digital readout; 3.75 in diameter quill w/no. 6 morse taper; speed ranges 3; hp at spindle 12.5; threads 73, 2-84tpi; bed 15.75 in. Wd; cross slide tvl 11.875 in.; compound rest travel 7.50 in.; tailstock center 6mt; tailstock tvl 7.00 in.; feeds per spindle rev 0.0016 - 0.11 in.; magnetic starter w/110 v controls; center distance 60.00 in.; constant surface speed/3 axis dro models; qc tool post; steady rest; follower rest; micro carriage stop; chuckguard; chipguard; taper attachment; 17 and 27 in. Face plate; 10.00 in. 3-jaw chuck; 12.00 in. 4-jaw chuck

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

T221-b