NSN 3416-01-407-0426

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-01-407-0426

| Mounting Type: |
|--|
| Floor |
| Current Type: |
| Ac |
| Center To Center Distance: |
| 40.000 inches |
| Performance Type: |
| Heavy duty |
| Purpose For Which Designed: |
| Toolroom |
| Design Type: |
| Screw |
| Electric Motor Horsepower Rating: |
| 15.0 |
| Bed Type: |
| Solid |
| Electric Motor Quantity: |
| 1 |
| Spindle Speed Quantity: |
| 18 or 36 |
| Spindle Speed Range In Rpm: |
| +27.0/+1600.0 |
| Rated Swing: |
| 20.000 inches |
| Swing Over Cross Slide: |
| 13.000 inches |
| Thread Change Quantity: |
| 93 |
| Headstock Drive Type: |
| Geared head |
| Headstock Center Taper Size Designator: |
| 5 morse |
| Hole Diameter Through Spindle: |
| 3.060 inches |
| Carriage Quantity: |
| 1 |
| Carriage Longitudinal Feed Operation Method: |
| Hand and power |
| Carriage Cross Feed Operation Method: |
| Hand and power |
| Thread Quantity Range: |
| +2.0/+72.0 per inch |

NSN 3416-01-407-0426

Engine Lathe - Page 2 of 2

Voltage In Volts:

T221-b



| 115.0 | | | | |
|---|-----------------------------|--------------------------|-----------------------------------|--|
| Reference Number Differentiating Characteristics: | | | | |
| As differentiated by center to center distance, | spindle speed range in rpm, | electric motor quantity, | electric motor horsepower rating, | |
| current, and frequency in hertz | | | | |
| Shelf Life: | | | | |
| N/a | | | | |
| Unit Of Measure: | | | | |
| | | | | |
| Demilitarization: | | | | |
| No | | | | |
| Fiig: | | | | |