

View Online at <https://aerobasegroup.com/nsn/3416-01-409-0348>

Mounting Type:

Floor

Current Type:

Ac

Current Rating In Amps:

110.0

Electric Motor Horsepower Rating:

56.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

4.500 inches

Maximum Chucking Distance Over Universal Carriage:

30.000 inches

Spindle Reversibility:

Reversible

Rated Swing:

30.000 inches

Actual Swing Over Bed:

21.000 inches

Swing Over Cross Slide:

21.000 inches

Maximum Distance From Spindle Nose To Turret Face:

40.500 inches

Universal Carriage Longitudinal Travel:

70.000 inches

Universal Carriage Cross Travel:

12.250 inches

Universal Carriage Feed Type:

Power

Turret Carriage Longitudinal Travel:

35.000 inches

Turret Carriage Feed Type:

Power

Turret Shape:

Hexagon or pentagon

Turret Position Quantity:

8 or 12

Voltage In Volts:

460.0

Phase:

Three

Special Features:

Qvariable spindle speed; live and static turret; spindle range 0-3007 rpm; 4 axis; twin upper and lower turret heads, 8 station turrets; max cap. 24 live tools; no. 5 morse taper; quill stroke 6 in.; cnc; 45 degrees slant carriage

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a