
Engine Lathe - Page 1 of 2





Mounting Type: Floor Current Type:

Ac

Center To Center Distance:

80.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

Toolroom

Design Type:

Screw

Electric Motor Horsepower Rating:

15.000

Bed Type:

Removable block gap

Electric Motor Quantity:

2

Spindle Speed Range In Rpm:

+20.0/+1800.0

Swing Over Cross Slide:

14.000 inches

Thread Change Quantity:

38

Rated Swing Through Open Gap:

31.000 inches

Actual Swing Through Open Gap:

23.000 inches

Rated Swing Over Closed Gap:

23.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

5 morse

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Power

Thread Quantity Range:

+2.0/+72.0 per inch

Voltage In Volts:

220.0

NSN 3416-01-432-7265

Engine Lathe - Page 2 of 2



Phase:

Three

Special Features:

Coolant system 1/8 hp; bed 13.50 in. Wd by 15.0 in. Dp; quill tvl 7.0 in.; 3 "v" bed ways construction; carriage cross slide tvl 12.25 in; space rqrd 45 in. By 140 in.

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T221-b