

View Online at <https://aerobasegroup.com/nsn/3416-01-436-4947>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Current Rating In Amps:**

40.0

**Design Type:**

Ram

**Feed Type:**

Power

**Electric Motor Horsepower Rating:**

10.000

**Power Source:**

Electric motor

**Maximum Bar Stock Diameter Accommodated:**

2.400 inches

**Maximum Chucking Distance Over Universal Carriage:**

7.320 inches

**Spindle Speed Quantity:**

3960

**Spindle Speed Range In Rpm:**

+40.0/+4000.0

**Spindle Reversibility:**

Reversible

**Rated Swing:**

16.500 inches

**Actual Swing Over Bed:**

16.500 inches

**Swing Over Cross Slide:**

11.700 inches

**Maximum Distance From Spindle Nose To Turret Face:**

30.000 inches

**Universal Carriage Longitudinal Travel:**

13.780 inches

**Universal Carriage Cross Travel:**

7.080 inches

**Universal Carriage Compound:**

Included

**Rotation Travel In Deg:**

360.0

**Turret Shape:**

Hexagon

**Turret Position Quantity:**

12

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Longitudinal and cross feed rangeis 0.0001 per (1) spindle revolution

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-a