

View Online at <https://aerobasegroup.com/nsn/3416-01-436-4947>

Mounting Type:

Floor

Current Type:

Ac

Current Rating In Amps:

40.0

Design Type:

Ram

Feed Type:

Power

Electric Motor Horsepower Rating:

10.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

2.400 inches

Maximum Chucking Distance Over Universal Carriage:

7.320 inches

Spindle Speed Quantity:

3960

Spindle Speed Range In Rpm:

+40.0/+4000.0

Spindle Reversibility:

Reversible

Rated Swing:

16.500 inches

Actual Swing Over Bed:

16.500 inches

Swing Over Cross Slide:

11.700 inches

Maximum Distance From Spindle Nose To Turret Face:

30.000 inches

Universal Carriage Longitudinal Travel:

13.780 inches

Universal Carriage Cross Travel:

7.080 inches

Universal Carriage Compound:

Included

Rotation Travel In Deg:

360.0

Turret Shape:

Hexagon

Turret Position Quantity:

12

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Longitudinal and cross feed range is 0.0001 per (1) spindle revolution

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a