

View Online at <https://aerobasegroup.com/nsn/3416-01-438-4322>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

20.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

No.3in-d1 spindle, 1ea; digital readout for x/z axis, 1ea; chip/coolant pan, 1ea; tail stk, 1ea; comp coolant system, 1ea

Design Type:

Plain

Electric Motor Horsepower Rating:

2.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+60.0/+2500.0

Rated Swing:

12.000 inches

Actual Swing Over Bed:

12.000 inches

Swing Over Cross Slide:

7.000 inches

Headstock Drive Type:

Gearhead

Headstock Center Taper Size Designator:

2 morse

Hollow Spindle Hole Size:

1.375 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

50

Gear Change Type:

Quick

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b