NSN 3416-01-438-4322

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-01-438-4322

| Mounting Type: |
|---------------------------------------------------------------------------------------------------------------------------|
| Floor |
| Current Type: |
| Ac |
| Center To Center Distance: |
| 20.000 inches |
| Performance Type: |
| Standard duty |
| Purpose For Which Designed: |
| Toolroom |
| Accessory Components And Quantity: |
| No.3in-d1 spindle, 1ea; digital readout for x/z axis, 1ea; chip/coolant pan, 1ea; tail stk, 1ea; comp coolant system, 1ea |
| Design Type: |
| Plain |
| Electric Motor Horsepower Rating: |
| 2.000 |
| Bed Type: |
| Solid |
| Electric Motor Quantity: |
| 1 |
| Spindle Speed Quantity: |
| 12 |
| Spindle Speed Range In Rpm: |
| +60.0/+2500.0 |
| Rated Swing: |
| 12.000 inches |
| Actual Swing Over Bed: |
| 12.000 inches |
| Swing Over Cross Slide: |
| 7.000 inches |
| Headstock Drive Type: |
| Geared head |
| Headstock Center Taper Size Designator: |
| 2 morse |
| Hollow Spindle Hole Size: |
| 1.375 inches |
| Carriage Quantity: |
| 1 |
| Carriage Longitudinal Feed Operation Method: |
| Hand and power |

Hand and power

Carriage Cross Feed Operation Method:

NSN 3416-01-438-4322 Engine Lathe - Page 2 of 2



| Carriage Feed Change Quantity: |
|--------------------------------|
| 50 |
| Gear Change Type: |
| Quick |
| Voltage In Volts: |
| 230.0 and 460.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T221-b