

View Online at <https://aerobasegroup.com/nsn/3416-01-448-3041>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

30.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Design Type:

Plain

Electric Motor Horsepower Rating:

5.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+50.0/+1800.0

Rated Swing:

15.000 inches

Actual Swing Over Bed:

15.000 inches

Swing Over Cross Slide:

8.000 inches

Thread Change Quantity:

45

Headstock Drive Type:

Gearhead

Headstock Center Taper Size Designator:

Morse

Hole Diameter Through Spindle:

2.000 inches

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+64.0 per inch

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Generic master for 3416-01-142-0949 and 3416-01-447-2320; morse taper isno 3; spindle nose size 6d-1

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b