

View Online at <https://aerobasegroup.com/nsn/3416-01-449-9193>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

60.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General or toolroom

Design Type:

Screw

Electric Motor Horsepower Rating:

10.000

Bed Type:

Removable block gap

Electric Motor Quantity:

4

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+20.0/+1600.0

Swing Over Cross Slide:

10.600 inches

Thread Change Quantity:

73

Rated Swing Through Open Gap:

28.700 inches

Actual Swing Through Open Gap:

28.700 inches

Rated Swing Over Closed Gap:

18.100 inches

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

5 morse

Hole Diameter Through Spindle:

3.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+84.0 per inch

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Generically grouped with 3416-01-237-6063 and 3416ncc617558

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b