

View Online at <https://aerobasegroup.com/nsn/3416-01-475-1178>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

40.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Headstock w/two speed range (20-400rpm low range) and (400-2500rpm high range)1ea; led display indicator 1ea;

Design Type:

Screw

Electric Motor Horsepower Rating:

5.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

2

Spindle Speed Range In Rpm:

+20.0/+400.0

Rated Swing:

14.000 inches

Actual Swing Over Bed:

14.812 inches

Swing Over Cross Slide:

8.375 inches

Thread Change Quantity:

45

Actual Swing Over Closed Gap:

21.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

6 morse or 4 morse

Hole Diameter Through Spindle:

2.062 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+72.0 per inch

Voltage In Volts:

230.0

Phase:

Three

Special Features:

Coolant system w/115.0vac motor and controls

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b