

View Online at <https://aerobasegroup.com/nsn/3416-01-479-0583>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

60.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Headstock w/four speed ranges (18-180rpms, low range), and (180-1800rpms, high range), (1ea); led indicator (1ea); 0.125hp coolant, 115vac (1ea)

Design Type:

Screw

Electric Motor Horsepower Rating:

10.000

Bed Type:

Removable block gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+18.0/+1800.0

Swing Over Cross Slide:

11.000 inches

Thread Change Quantity:

38 or 40

Rated Swing Through Open Gap:

28.000 inches

Actual Swing Through Open Gap:

28.000 inches

Rated Swing Over Closed Gap:

20.000 inches

Actual Swing Over Closed Gap:

18.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

7 morse or 5 morse

Hole Diameter Through Spindle:

3.062 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+72.0 per inch

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b