

View Online at <https://aerobasegroup.com/nsn/3416-01-532-1686>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

60.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Design Type:

Plain

Electric Motor Horsepower Rating:

15.000

Bed Type:

Removable block gap

Electric Motor Quantity:

2

Spindle Speed Range In Rpm:

+20.0/+2000.0

Rated Swing:

18.125 inches

Actual Swing Over Bed:

18.125 inches

Swing Over Cross Slide:

10.625 inches

Rated Swing Through Open Gap:

28.750 inches

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

6 morse

Hole Diameter Through Spindle:

3.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Spindle speed variable; hp at spindle 12.5

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b