
Engine Lathe - Page 1 of 2

Mounting Type:





Floor **Current Type:** Ac **Center To Center Distance:** 40.000 inches Performance Type: Standard duty **Purpose For Which Designed:** General **Design Type:** Plain **Operation Method:** Manual **Electric Motor Horsepower Rating:** 5.0 Bed Type: Permanent gap **Electric Motor Quantity:** 2 **Spindle Speed Quantity:** 1 Spindle Speed Range In Rpm: +20.0/+2500.0 **Actual Swing Over Bed:** 14.187 inches Swing Over Cross Slide: 8.375 inches **Thread Change Quantity:** 4 Actual Swing Through Open Gap: 21.000 inches Hole Diameter Through Spindle: 2.062 inches **Carriage Longitudinal Feed Operation Method:** Hand **Carriage Cross Feed Operation Method:** Hand **Product Name:** Manual lathe Voltage In Volts: 220.0

NSN 3416-01-601-0749

Engine Lathe - Page 2 of 2



Phase:

Single or three

Special Features:

Front loading chip tray for easier cleaning; footbrake; 81 (I) x 36 (w) x 60 (h); digital display; hardened and ground gears and bedways; cast iron machine

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T221-b