

View Online at <https://aerobasegroup.com/nsn/3417-01-149-8896>

Mounting Type:

Floor

Width:

10.000 inches

Length:

48.000 inches

Current Type:

Ac

Head Type:

Swivel

Furnished Items And Quantity:

Work lamp 1

Electric Motor Horsepower Rating:

3.000

Power Source:

Electric motor

Table Type:

Plain

Table Longitudinal Travel:

32.000 inches

Table Cross Travel:

12.000 inches

Spindle Type:

Vertical swivel graduated

Table Vertical Travel:

16.500 inches

Maximum Distance From Spindle Nose To Working Surface:

16.500 inches

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Special Features:

Three 0.625 in. Table t-slots; distance between table t-slots 2.250 in.; table handwheel dial graduations 0.001 in.; quill travel 5.250 in.; overarm travel 30.0 in.; center of spindle to column face 2.500 in. , 28.0 in. ; center of table to column face 5.0 in. , 17.0 in. ; head tilt front to back 45 degrees, head tilt back to front 45 degrees; head tilt side to side, left and right 90 degrees; standard r-8 spindle taper or no. 9 brown and sharpe taper; optional no. 30 mmt quick-change or no. 200 kwik-switch is available when specified; spindle speeds variable, back gear 50 rpm to 525 rpm, direct drive 400 rpm to 4200 rpm; reversible spindle rotation; quill feeds 0.0015 in., 0.003 in., 0.006 in.; quill diameter 3.375 in.; turret and overarm rotation 360 degrees; shipping weight approximately 3020 pounds

Frequency In Hertz:

60.0

Quantity:

1

Shelf Life:

N/a

Demilitarization:

No

Fig:

T221-d