

View Online at <https://aerobasegroup.com/nsn/3417-01-149-8896>

**Mounting Type:**

Floor

**Width:**

10.000 inches

**Length:**

48.000 inches

**Current Type:**

Ac

**Head Type:**

Swivel

**Furnished Items And Quantity:**

Work lamp 1

**Electric Motor Horsepower Rating:**

3.000

**Power Source:**

Electric motor

**Table Type:**

Plain

**Table Longitudinal Travel:**

32.000 inches

**Table Cross Travel:**

12.000 inches

**Spindle Type:**

Vertical swivel graduated

**Table Vertical Travel:**

16.500 inches

**Maximum Distance From Spindle Nose To Working Surface:**

16.500 inches

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Special Features:**

Three 0.625 in. Table t-slots; distance between table t-slots 2.250 in.; table handwheel dial graduations 0.001 in.; quill travel 5.250 in.; overarm travel 30.0 in.; center of spindle to column face 2.500 in. , 28.0 in. ; center of table to column face 5.0 in. , 17.0 in. ; head tilt front to back 45 degrees, head tilt back to front 45 degrees; head tilt side to side, left and right 90 degrees; standard r-8 spindle taper or no. 9 brown and sharpe taper; optional no. 30 mmt quick-change or no. 200 kwik-switch is available when specified; spindle speeds variable, back gear 50 rpm to 525 rpm, direct drive 400 rpm to 4200 rpm; reversible spindle rotation; quill feeds 0.0015 in., 0.003 in., 0.006 in.; quill diameter 3.375 in.; turret and overarm rotation 360 degrees; shipping weight approximately 3020 pounds

**Frequency In Hertz:**

60.0

**Quantity:**

1

**Shelf Life:**

N/a

**Demilitarization:**

No

**Fig:**

T221-d