

View Online at <https://aerobasegroup.com/nsn/3417-01-208-1739>

Mounting Type:

Floor

Current Type:

Ac

Furnished Items And Quantity:

1 4.5 hp feed motor; 1 mechanical coolant system; 1 splash tray; 1 set of manuals; 2 horizontal arobr supports; 1 set of spanners; 1 cutter guard

Feed Type:

Power

Electric Motor Horsepower Rating:

10.000

Power Source:

Electric motor

Table Longitudinal Travel:

35.400 inches

Table Cross Travel:

12.000 inches

Table Vertical Travel:

17.700 inches

Table Swivel Direction And Adjustment In Deg:

45.0 each side

Maximum Distance From Spindle Center To Table Top:

17.700 inches

Electric Motor Fungus Resistant Feature:

Provided

Electric Motor Radio Interference Suppression:

Not included

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Special Features:

Four 0.866 in. T-slots at 3.150 in. Centers; spindle nose diameter 5.062 in.; spindle internal taper no. 50 american standard; no. Of spindle speeds in either direction 18; low spindle speed range 18 rpm to 1062 rpm, high spindle speed range 27 rpm to 1565 rpm; infinitely variable longitudinal and cross feed range 0.75 in. Per minute to 72.0 in. Per minute, infinitely variable vertical feed range 0.25 in. Per minute to 16.0 in. Per minute; rapid traverse lon gitudinal and cross feed range 120 in. Per minute, rapid traverse vertical feed range 35 in. Per minute; floor space 107 in. By 106 in.; net weight 10299 pounds; gross weight 11200 pounds; shipping sizes 87 in. By 114 in. By 108 in.

Frequency In Hertz:

60.0

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

Fig:

T221-d