

View Online at <https://aerobasegroup.com/nsn/3417-01-208-1739>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 4.5 hp feed motor; 1 mechanical coolant system; 1 splash tray; 1 set of manuals; 2 horizontal arobr supports; 1 set of spanners; 1 cutter guard

**Feed Type:**

Power

**Electric Motor Horsepower Rating:**

10.000

**Power Source:**

Electric motor

**Table Longitudinal Travel:**

35.400 inches

**Table Cross Travel:**

12.000 inches

**Table Vertical Travel:**

17.700 inches

**Table Swivel Direction And Adjustment In Deg:**

45.0 each side

**Maximum Distance From Spindle Center To Table Top:**

17.700 inches

**Electric Motor Fungus Resistant Feature:**

Provided

**Electric Motor Radio Interference Suppression:**

Not included

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Special Features:**

Four 0.866 in. T-slots at 3.150 in. Centers; spindle nose diameter 5.062 in.; spindle internal taper no. 50 american standard; no. Of spindle speeds in either direction 18; low spindle speed range 18 rpm to 1062 rpm, high spindle speed range 27 rpm to 1565 rpm; infinitely variable longitudinal and cross feed range 0.75 in. Per minute to 72.0 in. Per minute, infinitely variable vertical feed range 0.25 in. Per minute to 16.0 in. Per minute; rapid traverse lon gitudinal and cross feed range 120 in. Per minute, rapid traverse vertical feed range 35 in. Per minute; floor space 107 in. By 106 in.; net weight 10299 pounds; gross weight 11200 pounds; shipping sizes 87 in. By 114 in. By 108 in.

**Frequency In Hertz:**

60.0

**Quantity:**

2

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

T221-d