

View Online at <https://aerobasegroup.com/nsn/3418-00-242-5961>

Mounting Type:

Floor

Width:

15.000 inches

Length:

18.250 inches

Current Type:

Ac

Furnished Items And Quantity:

12 bits, carbide tipped, 7/16 in. Sq, 3-1/2 in. Lg; 12 bits, carbide tipped, 1/2 in. Sq, 3-1/2 in. Lg; 12 bits, hss, 7/16 in. Sq, 3-1/2 in. Lg; 12 bits, hss, 1/2 in. Sq, 3-1/2 in. Lg; 1 set index centers, head and trail stocks and base swing diameter of 10 in. Min up to 13 in. Between centers; 1 tool holder, lh, 7/8 in. By 1-3/4 in. Shank for 1/2 in. Sq bits; 1 tool holder, rh, 7/8 in. By 1-3/4 in. Shank for 1/2 in. Sq bits; 1 tool holder, shaper extension, 3/4 in. By 1-5/8 in. Shank w/bar 1-1/8 in. Diameter by 14 in. Lg to take 7/16 in. Sq bits; 1 tool holder, straight 7/8 in. By 1-3/4 in. Shank for 1/2 in. Sq bits

Face Type:

Tilting

Electric Motor Horsepower Rating:

10.000

Power Source:

Electric motor

Radio Interference Suppression:

Included

Table Type:

Universal

Ram Stroke Length:

25.000 inches

Ram Head Vertical Feed:

9.500 inches

Back Geared Feature:

Not included

Hydraulically Operated Feature:

Not included

Table Horizontal Travel Distance:

30.500 inches

Table Vertical Travel Distance:

13.000 inches

Rapid Traverse Direction:

Horizontally to table or vertically to table

Ram To Table Maximum Distance:

17.125 inches

Fungus Resistant Treatment:

Included

Voltage In Volts:

220.0

Phase:

Frequency In Hertz:

60.0

Quantity:

1

Specification Or Standard:

2 type and 2 size

Departure From Cited Designator:

Elec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-g