NSN 3419-00-194-9240

Pipe And Bolt Threading Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3419-00-194-9240

Thread Direction:
Right-hand
Thread Size:
$0.250 \; \text{in. And} \; 0.312 \; \text{in. And} \; 0.375 \; \text{in. And} \; 0.438 \; \text{in. And} \; 0.500 \; \text{in. And} \; 0.562 \; \text{in. And} \; 0.625 \; \text{in. And} \; 0.750 \; \text{in. And} \; 0.875 \; \text{in. And} \; 1.000 \; \text{in. And} \; 0.500 \; \text{in. And} \; 0.500 \; \text{in. And} \; 0.500 \; \text{in. And} \; 0.625 \; \text{in. And} \; 0.750 \; \text{in. And} \; 0.875 \;$
1.000 in. And 1.125 in. And 1.250 in. And 1.375 in. And 1.500 in. And 1.500 in. And 1.750 in. And 1.750 in. And 2.000 in. And 0.125 in. And
0.375 in. And 0.500 in. And 1.000 in. And 1.250 in. And 1.500 in. And 2.000 in. And 0.750
Current Type:
Ac
Screw Thread Series Designator:
Unc
Reamer Type:
Multiblade
Electric Motor Horsepower Rating:
0.5
Mounting Type For Which Designed:
Bench
Spindle Type:
Single
Minimum Pipe Size Accommodated:
0.125 inches
Maximum Pipe Size Accommodated:
2.000 inches
Minimum Bolt Diameter Accommodated:
0.250 inches
Maximum Bolt Diameter Accommodated:
2.000 inches
Die Head Quantity:
1
Die Head Type:
Quick opening
Die Head Design:
Stationary
Thread Cutting Chaser:
Included
Set Quantity:
14
Cutting Device Type:
Wheel
Voltage In Volts:
110.0
Phase:
Single

60.0

Frequency In Hertz:

NSN 3419-00-194-9240

Pipe And Bolt Threading Machine - Page 2 of 2



I type and 1 class and a style and 2 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-I