Buffing And Polishing Machine - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3419-00-529-0820

Current Type: Ac Horsepower Rating: 0.50 Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Distance Between Flanges: 0.625 inches Voltage In Volts: 110.0 Phase: Single Frequency In Hertz: 60.0 Quantity: 1 Sheff Life: Na Distance: Te Demiliarization: No Fig: 728-n	
Horsepower Rating: 0.50 Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 0.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: 11.0 Phase: Single Frequency In Hertz: 60.0 Quantity: 1 Shelf Life: Na Mai Mai Mai Mai Frequency In Hertz: Na Distance: Na Distance: Na Distance: Na Distance: Na Distance: Na	
0.50Power Source:Electric motorMounting Type For Which Designed:BenchSpindle End Type:DoubleSpindle Speed In Rpm:3450.0Distance From Spindle Center To Mounting:0.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:11.0.0Phase:0.3.0SingleFrequency In Hertz:60.0Countiny:11Shelf Life:NaUit Of Measure:Poillainzetation:NoFig:Fig:	
Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Volage In Volts: 110.0 Phase: Single Guantity: 1 Maint Spiel Life: N/a Lift Measure: Ind Spiel Life: N/a Spiel Life: N/a Ent of Measure: Image: Spiel Life: N/a Spiel Life: N/a Ent of Measure: Image: Spiel Life: N/a Ent of Measure: Image: Spiel Life: Spiel Life: Spiel Life:	
Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: 110.0 Phase: Single Guantity: 1 1 Maint Maint Maint Shelf Life: N/a Chi Of Measure: - Femiliatrization: No Fig:	
Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: 110.0 Phase: Single Frequency In Hertz: 60.0 Quantity: 1 Na Shelf Life: Na Ditt Of Measure: - Pomilitarization: No Fig:	
Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Distance From Spindle Center To Mounting: 9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: 110.0 Phase: Single Guantity: 1 Sheft Life: Na Ditt Of Measure: Image: Na Pomilitarization: No Fig:	
Spindle End Type:DoubleSpindle Speed In Rpm:3450.0Distance From Spindle Center To Mounting:9.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:110.0Phase:SingleCuantity:11Shift Life:N/aUnd Measure:-Philtarization:NoFig:Fig:	
DoubleSpindle Speed In Rpm:3450.0Distance From Spindle Center To Mounting:9.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:110.0Phase:SingleGo.0Cuantity:1Sheff Life:N/aUnit Of Measure:Penilitarization:NoFig:Fig:	
Spindle Speed In Rpm:3450.0Distance From Spindle Center To Mounting:9.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:10.0Phase:SingleFrequency In Hertz:60.0Quantity:1Shelf Life:NaUnit Of Measure:-Pensilitarization:NoFig:Fig:	
3450.0Distance From Spindle Center To Mounting:9.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:10.0Phase:SingleFrequency In Hertz:60.0Quantity:1Sheff Life:N/aDistof Measure:Femilitarization:NoFig:Fig:	
Distance From Spindle Center To Mounting:9.000 inchesDistance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:110.0Phase:SingleFrequency In Hertz:60.0Quantity:11Shelf Life:N/aDint Of Measure:-Demilitarization:NoFig:	
9.000 inches Distance Between Inside Wheel Flanges On Spindle: 0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: 10.0 Phase: 110.0 Phase: Single Frequency In Hertz: 60.0 Cuantity: 60.0 Cuantity: 1 Shelf Life: N/a Diff Life: N/a Fig:	
Distance Between Inside Wheel Flanges On Spindle:0.750 inchesSpindle Diameter Between Flanges:0.625 inchesVoltage In Volts:110.0Phase:SingleFrequency In Hertz:60.0Quantity:1Shelf Life:N/aUnit Of Measure:-Phase:SingleFrequency In Hertz:60.0Buttity:11Shelf Life:N/aFrequency:	
0.750 inches Spindle Diameter Between Flanges: 0.625 inches Voltage In Volts: Voltage In Volts: 110.0 Phase: Single Frequency In Hertz: 60.0 Guantity: 1 Shelf Life: N/a Unit Of Measure: Fmeiliarization: No Fig:	
Spindle Diameter Between Flanges:0.625 inchesVoltage In Volts:110.0Phase:SingleFrequency In Hertz:60.0Quantity:1Shelf Life:N/aUnit Of Measure:Pomilitarization:NoFig:	
0.625 inches Voltage In Volts: 110.0 Phase: Single Frequency In Hertz: 60.0 Quantity: 1 Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Voltage In Volts:110.0Phase:SingleFrequency In Hertz:60.0Quantity:1Shelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
<pre>110.0 Phase: Phase: Single Frequency In Hertz: 60.0 Quantity: 1 Shelf Life: N/a Unit Of Measure: Pomilitarization: No</pre>	
Phase:SingleFrequency In Hertz:60.0Quantity:1Shelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	
Single Frequency In Hertz: 60.0 Quantity: 1 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Frequency In Hertz: 60.0 Quantity: 1 1 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Phase:
60.0 Quantity: 1 1 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Single
Quantity: 1 5helf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Frequency In Hertz:
1 Shelf Life: N/a Unit Of Measure: Demilitarization: No	60.0
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Quantity:
N/a Unit Of Measure: Demilitarization: No	1
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
T284-n	Fiig:
	T284-n