

View Online at <https://aerobasegroup.com/nsn/3431-01-165-4566>

**Mounting Type:**

Base and wheel

**Wheel Quantity:**

4

**Accessory Components And Quantity:**

2 in o.D. Spindle kit, 1; readi-reel adapter, 1; solenoid-valve kit, 1; stitch timer/spot timer/burnback kit, 1; 25 foot wire extension assembly, 1; 25 or 50 foot power input cable with plug, 1; gas cylinder mounting & undercarriage, 1; undercarriage, 1; drive rolls and guide tube kits, 1; wire drive conversion kits for aluminum electrode, 2

**Tire Type:**

Solid rubber and steel

**Power Output Rating:**

Not rated

**Output Current Type:**

Ac

**Output Voltage Rating In Volts:**

115.0

**Output Current Rating In Amps:**

200.0

**Design Type:**

Rectifier

**Output Frequency Rating:**

Not rated

**Output Phase:**

Single

**Arc Current Type:**

Dc

**Minimum Current At Specificationified Voltage:**

165 amp at 15 v

**Maximum Current At Specificationified Voltage:**

220 amp at 17 v

**Operator Type For Which Designed:**

Multiple

**Remote Control Design:**

Not included

**Auxiliary Power Output Design:**

Included

**Special Features:**

Eara-te

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T345-a