

View Online at <https://aerobasegroup.com/nsn/3431-01-368-8324>

Mounting Type:

Base

Current Type:

Ac or dc

Output Current Type:

Ac

Output Voltage Rating In Volts:

115.0

Output Current Rating In Amps:

Between 200.0 and 300.0

Design Type:

Rectifier

Output Frequency Rating:

60.0 hertz

Output Phase:

Single

Arc Current Type:

Ac or dc

Remote Control Design:

Not included

Auxiliary Power Output Design:

Included

Voltage In Volts:

200.0 or 230.0 or 460.0

Phase:

Single

Special Features:

Delivers 300amps dc at 50% duty cycle for gma (mig), smaw(stick), and gtaw(tig); 200amp at 40% duty cycle squarewave balanced ac output for smaw and gtaw with optional hf unit; multiprocess capabilities; dual output studs foreasy hook-up; 115 vac/15amp duplex hookup w/circuit breaker protection; 24vac contactor and wire feeder control w/10amp circuit breaker protection; ac-dc, dc-cv, cc selector switch; output contactor switch; amp/volt control switch; variable arc control; shipping weight is 380lbs (172kg)

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T345-a