

View Online at <https://aerobasegroup.com/nsn/3431-01-384-5273>

**Mounting Type:**

Base

**Current Type:**

Ac or dc

**Output Current Type:**

Ac

**Output Voltage Rating In Volts:**

115.0

**Output Current Rating In Amps:**

350.0

**Design Type:**

Rectifier

**Output Frequency Rating:**

60.0 hertz

**Output Phase:**

Single

**Arc Current Type:**

Ac or dc

**Minimum Current At Specificationified Voltage:**

300 amp at 32 v

**Maximum Current At Specificationified Voltage:**

350 amp at 34 v

**Operator Type For Which Designed:**

Single

**Remote Control Design:**

Included

**Auxiliary Power Output Design:**

Included

**Voltage In Volts:**

230.0 or 460.0

**Phase:**

Single

**Special Features:**

Solid-state contactor; polarity switch; adjustable gas post-flow timer; built in adjustable high frequency; square wave ac welding; line voltage compensation; silicon controlled rectifier; semi or automatic weld programming; led digital meters; presetting amperage for welding; 0 to 10 volt reference; height 47 1/4 in.; width 24 in.; depth 22 3/4 in.; weight 549 pounds

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T345-a