NSN 3431-01-596-2069

Gas Shielded Arc Welding Torch Outfit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3431-01-596-2069

Model Number:

Millermatic 211 auto-set with mvp

Special Features:

Comes complete with power source; 6 f (1.8m) power cord and mvp plugs; 10 ft(3 m)m-100 mig gun and cable assembly; 10 ft(3 m) work cable and clamp; smith argon and ar/c02 mix regulator/flow gauge with hose; spool of hobart .030 in(0.8 mm) solid wire; two contact tips for .030 in(0.8 mm)wire and two contact tips for .035 (0.9 mm) wire; dual-groove quick-change drive roll for .024 in(0.6 mm) or .030/.035 in(0.8/0.9 mm) wire; factory-installed gas solenoid valve; set-up and operation cd; information/settings chart; material thickness guage.

Supplementary Features:

Input power 230 v, 25 a, 60 hz, single-phase; 120 v, 20 a, 60 hz, single-phase; rated output 150 a at 23.5 vdc, 30% duty cycle (230 v); 90 a at 20 vdc, 20% dutycycle (120 v); amperage range 30-210 a, max. Open-circuit voltage 34.

n/a
Unit Of Measure:
Demilitarization:

Shelf Life:

No Fiig:

A23800