## NSN 3439-00-460-7683

Welding Electrode - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3439-00-460-7683

Outside Diameter:

| Outside Diameter:   |
|---|
| 0.078 inches  |
| Length:   |
| 9.000 inches  |
| Current Type:   |
| Dc  |
| Quantity Within Each Unit Package:  |
| 6.0 pounds  |
| Weld Position For Which Designed:   |
| All positions   |
| Polarity Characteristic:  |
| Reverse   |
| Flux Coating Type:  |
| Shielded arc  |
| Criticality Code Justification:   |
| Zzzx  |
| Deposited Filler Metal Chemical Composition In Percent:                                     |
| 2.50 manganese third element  |
| Material:   |
| Stainless steel filler  |
| Unit Package Type:  |
| Can   |
| Shape:  |
| Round   |
| Specification Or Standard:  |
| Mil-316l-15 type  |
| Departure From Cited Designator:  |
| Material controlled iaw navsea 0948-lp-045-7010 material control standard for level i items |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A283a0  |
| Mil-std (military Standard):  |
| spec.   |