## NSN 3439-01-623-8186

**Fiig:** T166-j

Soldering-desoldering Station - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3439-01-623-8186 **Current Type:** Ac Frequency In Hertz: Between 50.0 and 60.0 **Operating Voltage In Volts:** 230.0 Tip Removability: Removable **Dual Heat Control:** Included Spotlight: Not included **Thermostatic Control:** Not included Wattage Rating In Watts: 207.0 **Features Provided:** Visual indicating thermometer **Product Name:** Mbt 250 digital sdtp rework & repair system Phase: Three **Special Features:** Sensatemp only handpiece; tip to ground resistance 20hms or less; tip temperature range 38 to 482c; pressure 0.48 bar at maximum setting; airflow 9slpm max; quiet flow pump for vacuum and pressure; operates 3 handpiece simultaneously; automatic tip offset compensation system; automatic or manual tip temperature setback and power down, constant memory; comes with ps-90 universal soldering iron, sx-90 sodr-x-tractor, tt-65 thermotweez, tp-65 thermopik, mbt 250 power supply and a tip maintenance system which includes the sponge tray, sponge tool and fiber tool Shelf Life: N/a **Unit Of Measure: Demilitarization:** No