

View Online at <https://aerobasegroup.com/nsn/3442-01-381-6819>

Special Features:

Direct coupled pump flange motors; movable cylinder giving more side movement of the ram since the cylinder does not house the pump and motor; adjustable relief valve; table is adjustable with self-locking table winch; equipped with safety devices to prevent over extension of the ram, and over capacity of the press

General Description:

G100 ton capacity; frame uprights 1 1/2 in. By 5 in.; head, bed rails, 15 in. Channel; base members 5 in. Channel; width between uprights 48 in.; width between table rails 15 in.; table travel 30 in.; vertical clearance 36 1/2 in.; bed support pins 2 in. Diameter; bed support pins 2 each; inside uprights 12 in.; ram travel 14 in.; ram diameter 3 1/4 in.; cylinder bore 6 in. Diameter; table spacing increments 6 in.; length 87 in.; width 48 in.; height 99 in.; left to right cylinder movement 31 in.; shipping weight 2858 pounds; 220/440 volt; three phase; 60 cycle; 5 horsepower; no load capaci type 7.5 in. Per minute; half capaci type 6.4 in. Per minute; full capaci type 5.3 in. Per minute; magnetic starter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23900