

View Online at <https://aerobasegroup.com/nsn/3442-01-382-0747>

**Special Features:**

Movable cylinder; cylinder and pump are separated on press giving more side movement of the ram since the cylinder does not house the pump and motor; adjustable relief valve; adjustable table with self locking table winch; equipped with safety devices to prevent over extension of the ram, and over capacity of the press

**General Description:**

B80 ton capacity; frame uprights 1 in. By 3 1/2 in. Rectangle; head, bed rails, 12 in. Channel; base members 4 in. Channel; width between uprights 48 in.; width between table rails 8 in.; table travel 32 in.; vertical clearance 41 in.; bed support pins 1 in. Diameter; 6 bed support pins; inside uprights 6 in.; ram travel 14 in.; ram diameter 3 1/4 in. Diameter; cylinder bore 5 in. Diameter; table spacing increments 4 in.; length 83 in.; width 39 in.; height 85 in.; left to right cylinder movement 34 in.; shipping weight 1403 in.; 5 horsepower; 220/440 volt; three phase; 60 cycle; ram speed no load 12 in. Per minute; ram speed half capaci type 9.0 in.; ram speed full capaci type 7.2 in. Per minute

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23900