

View Online at <https://aerobasegroup.com/nsn/3442-01-382-0787>

Special Features:

Movable cylinder; cylinder and pump are separated on press giving more side movement of the ram since the cylinder does not house the pump and motor; adjustable relief valve; adjustable with self locking table winch; equipped with safety devices to prevent over extension of the ram, and over capacity of the press

General Description:

40 ton capacity; fram uprights, 7 in. Channel; head, bed rails, 8 in. Channel; base members 3 in. By 2 in. Angle; width between uprights 30 1/4 in.; width between table rails 7 in.; table travel 36 in.; vertical clearance 41 1/2 in.; bed support pins 7/8 in. Diameter; 4 bed support pins; ram travel 14 in.; ram diameter 2 3/4 in.; cylinder bore 3 1/2 in. Diameter; table spacing increments 4 in.; length 63 in.; width 30 in.; height 82 in.; left to right cylinder movement 21 in.; shipping weight 820 pounds; 5 horsepower, 220/440 volt; three phase; 60 cycle; ram speed no load 24 in. Per minute; ram speed half capacity 18.5 in. Per minute; ram speed full capacity 14.5 in. Per minute

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23900