

View Online at <https://aerobasegroup.com/nsn/3442-01-382-0867>

Special Features:

Movable cylinder; cylinder and pump are separated on press giving more side movement of the ram since the cylinder does not house the pump and motor; adjustable relief valve; adjustable table with self locking table winch; equipped with safety devices to prevent over extension of the ram, and over capacity of the press

General Description:

60 ton capacity; frame uprights 1 in. By 3 1/2 in. Rectangle; head, bed rails, 10 in. Channel; base members 4 in. Channel; width between uprights 40 in.; width between table rails 8 in.; table travel 36 in.; vertical clearance 42 in.; bed support pins 1 in. Diameter; 4 bed support pins; inside uprights 6 in.; ram diameter 3 1/4 in.; cylinder bore 5 in. Diameter; table spacing increments 6 in.; length 75 in.; width 39 in.; height 83 in.; left to right cylinder movement 26 in.; shipping weight 1345 pounds; 5 horsepower; 220/440 volt; three phase; 60 cycle; ram speed no load 12 in. Per minute; ram speed half capaci type 9.5 in. Per minute; ram speed full capaci type 8.2 in. Per minute

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900